

AJ-800



Versatile Digital Inkjet Printer for professional packaging and paper bag production



PRINT RESOLUTION

Up to 1200 x 1200 dpi



PRINT SPEED

6, 12, 18 ips
(9, 18, 27 m/min)



PRINT WIDTH

Max: 17" (432 mm)



PRINT HEIGHT ADJUSTMENT

Up to 8" (203 mm)



INK

Dye or Pigment



INDUSTRY 4.0 READY



WATER BASED SUSTAINABLE PRINTING

- LOWEST OPERATING COST IN THE DIGITAL OVERPRINTING INDUSTRY
- DIVERSE APPLICATION COVERAGE WITH DYE OR PIGMENT INK OPTIONS
- PRINT ONTO CORRUGATED BOXES, PAPER BAGS, WOODEN BOXES AND OTHER PACKAGE TYPES
- QUICK JOB CHANGES BETWEEN DIFFERENT DESIGNS AND PACKAGING MATERIALS
- EASY OPERATION AND MAINTENANCE

Technical Specifications

Operation

Print Resolution	Up to 1200 x 1200 dpi
Print Speed	6 ips (9 m/min) @ 1200 x 1200 dpi 12 ips (18 m/min) @ 1200 x 600 dpi 18 ips (27 m/min) @ 1200 x 300 dpi
Print Width	Up to 17" (432 mm)
Feed Width	Up to 31" (787 mm)
Print Height	Adjustable up to 8" (203 mm)
Connectivity	1000 BaseT Ethernet, RJ-45 connection
Operating System	Microsoft Windows® 11/10
Software	AstroNova Control Software Package InEdit RIP Software (required, purchased separately)
Internet Access	24 hrs/day, 7 days/week for real-time diagnostics Every 15 days and during ink changeovers (minimum)

Environment & Physical

Conditions for Operation	Between 68° F to 86° F (20° C to 30° C), 50% to 70% Relative Humidity (non-condensing)
Conditions for Storage	Between 41° F to 122° F (5° C to 50° C) at RH up to 85%, non-condensing at 149° F (65° C)
Power Requirements	230V/115V AC +/-10%, Single Phase + Neutral, 50/60Hz, 16AMP 3000W with manual feed 3700W with Automatic Bag Feeder
Regulatory Compliance	UL 508A, CE
Dimensions (without automatic feeder)	119.9" L x 86.9" W x 61.3" H 3047 mm x 2206 mm x 1558 mm
Weight	2381 lbs. (1080 Kg) without automatic feeder

Supplies

Ink Type	High-Performance CYMK water-based pigment or dye, 5 Kg tanks
Material Types	Corrugated Cardboard, Flat die-cut boxes, pizza boxes, envelopes, padded envelopes, paper bags and other sustainable packaging materials

Maintenance

Maintenance System	Integrated, automatic printhead wiper and vacuum suction with user-replaceable cleaning pads
---------------------------	--

Suction Cup Automatic Bag Feeder (Optional)

Material Size	19.7" x 16.5"(Max, excluding handles) 500 mm x 419 mm 9.4" x 7.0" (Min, excluding handles) 239 mm x 178 mm
Feed Speed	Sync with AJ-800
Compressed Air	87 psi, 1.77 CFM Quick connector fitting for Ø8mm

Automatic High-Speed Commercial Vacuum Friction Feeder VF-280 (Optional)

Material Size	3" x 5" (76 mm x 127 mm) Min 29"x28" (736 mm x 711 mm) Max
Material Thickness	Up to 1" (25 mm)
Electrical	110/220V AC, Single Phase, 10A circuit
Interlock	Dry Contact (Low Volt) Standard Operator
Controls	Power (On/Off), Vacuum (On/Off), Stop, Jog, Start, Feed Speed
Physical	24" L x 37.5" W x 33-36" H 609 mm x 952 mm x 838-914 mm

What's Included

AstroJet AJ-800 Printer, Set printheads (2), Manual Infeed Table, Long Belt, Exit Tray (ink purchased separately)

Warranty

One-year Manufacturer's Parts & Labor Warranty on printer and accessories

2 years from date of production on unused/unopened ink tanks, 6 months if opened or installed



Toll-free: 877-757-7978 | Tel: 401-828-4000 | astronovaproductid.com